



**FEATURES & OPTIONS**

**KEY SPECIFICATION - ELITE 910**

Structure	Rectangular 6" x 8" structure made of high tensile steel
Pivots	2" diameter heat-treated and chromed pins mounted on bronze bushings
Stabilizers	3" bore, 2" rod
Complete motion	Main: 9 sec w/ 19 gpm Stick: 7 sec w/ 19 gpm
Slewing ring	27" outside diameter
Rotation speed	9 rpm
Weight	4,940 lbs (with standard boom)
Operating pressure	3,000 psi
Swing torque	Theoretical: 15,987 ft. lb @ 3,200 psi Actual: Estimated at 13,589 ft. lb

**BOOM LENGTH OPTIONS - ELITE 910**

Standard	22'
Non-telescopic	21', 25' (other lengths available upon request)
Telescopic	26', 27' (other lengths available upon request)

**KEY SPECIFICATION - ELITE 915**

Structure	Rectangular 7"x 8" structure made of high tensile steel
Pivots	2.5" diameter heat-treated and chromed pins mounted on bronze bushings
Stabilizers	3.5" bore, 2" rod
Complete motion	Main: 9 sec w/ 22 gpm Stick: 8 sec w/ 22 gpm
Slewing ring	28" outside diameter
Rotation speed	8 rpm
Weight	6,163 lbs (with standard boom)
Operating pressure	3,200 psi

**BOOM LENGTH OPTIONS - ELITE 915**

Standard	23'
Telescopic	26', 28'

**ELITE 910 - APPROXIMATE LIFT CAPACITY (lbs)**

		DISTANCE FROM CENTER OF ROTATION (ft)			
		5	10	15	20
ELITE 910 T&T - M-22'	HEIGHT (ft)				
	30	6,520			
	25			5,200	
	20			5,290	3,920*
	15	7,660*	7,690	5,670	4,390
	10	3,580*	8,770	5,890	4,150
	5	5,380*	8,160	5,350	3,070
	0		5,500	3,390	

**SWING SYSTEM - ELITE 910/915**

- Features
- Continuous 360° rotation
  - Pedal activated rotation
  - Locking mechanism for transportation mode

**CYLINDERS - ELITE 910/915**

- Features
- Bolt-on head
  - Wear ring
  - Chrome plated tempered steel rod

**BOOM - ELITE 910/915**

- Features
- Induction tempered, chrome steel pins on bronze bushings
  - Telescopic booms activated by electric button and proportionately controlled by lever
  - Designed for closer access to loader frame
  - 2 x 55 W halogen work lights
  - Main/Stick boom: 5" bore, 3" rod

**HYDRAULIC SYSTEM - ELITE 910/915**

- Features
- Double function joystick
  - 2 x 19 gpm @ 1,800 rpm pump flow (910)
  - 2 x 22 gpm @ 2,100 rpm pump flow (915)
  - 8 port hydraulic oil manifold

**ELITE 915 - APPROXIMATE LIFT CAPACITY (lbs)**

		DISTANCE FROM CENTER OF ROTATION (ft)			
		5	10	15	20
ELITE 915 T&T - M-23'	HEIGHT (ft)				
	30			4,500*	
	25			5,490	
	20		6,680	5,760	5,090
	15	10,960***	8,660	6,430	5,220
	10	2,160*	10,390	7,000	5,240
	5	5,060*	10,300	6,860	4,650
0	8,720*	8,160	5,380		

\* Limited by stick boom hydraulic capacity

\*\* Lift capacities calculated at 100% operating pressure

\*\*\* Maximum load that must never be exceeded = 10,960 lbs

\*\*\*\* We reserve the right to change specification and improve our products without notice or obligation

**ROTOBEC LOCATIONS**

CANADA EAST/  
INTERNATIONAL  
Sainte Justine, QC  
Tel: 418.383.3002

USA EAST, CENTRAL  
Littleton, NH  
Tel: 603.444.2103

USA SOUTH  
Dallas, TX  
Tel: 972.242.9516

USA/CANADA WEST  
Kelowna, BC  
Tel: 250.765.1161



ELITE 910

ELITE 915